

Item : **Item 16**
 Typ : **Cubic**

FRIGA-BOHN

3C-E 3245 L (Multi Refrigerant)



Total capacity : 4,35 kW **DT1 (Dew) / DTM (Mean) :** 8 / 8,2 K

Operating conditions

Refrigerant : R404A
 Room temperature : 0 °C
 Unit number : 1

Thermal capacity (per unit)

Capacity per unit : 4,35 kW
 DT1 (Dew) / DTM (Mean) : 8 / 8,2 K

Coil characteristics (per unit)

Surface : 14.2 m²
 Volume : 3,2 dm³
 Fin spacing : 6 mm

Dimensional characteristics (per unit)

Empty net weight : 25 kg
 Packaging (L/D/H) : 1150 / 560 / 510 mm
 Packed unit weight : 31 kg
 Standard packaging : Cardboard box

Aeraulic characteristics (per unit)

Nb. and diameter of fans : 2 x 300 mm
 Air flow-rate : 2220 m³/h
 Pressure : 0 Pa
 Air throw : 16 m
 Lp (at 4m) : 34 dB(A)

Electrical characteristics (per unit)

Rotation speed : 1350 tr/min
 Maximum input power : 2 x 100 W
 Maximum operating current : 2 x 0,7 A
 Motor coupling : -
 Voltage/ Nb Phases / Frequency : 230V / 1 / 50-60Hz

(1) The average acoustic pressure level in dB(A) measured at 4 m, at fan height, in direct line of sight on a reflective surface, are given as an example. Only the acoustic pressure spectrum and Lw value, are contractually binding and may be used to evaluate the pressure characteristics at the property boundaries.

GACO SARL - -

28, Rue Bencharif Madani

25000 BELLEVUE / CONSTANTINE - ALGERIE

Tel. : 031 92 54 56 / 031 93 22 23 - Fax : 031 92 13 45

Email : gacosarl@gmail.com / benkobbi_fares@yahoo.fr



Item : **Item 16**



Typ : **Cubic**

Options 3C-E 3245 L

- ☒ E1U : Light electric defrost: 3 coil heaters
- ☐ E1K : Light electric defrost: 3 coil heaters
- ☐ E2K : Intermediate electric defrost: 2 coil heaters + 1 drain pan heater.
- ☐ E3K : Full electric defrost: 5 coil heaters + 1 drain pan heater.
- ☐ BXT : Blygold Polual XT coil protection.
- ☐ BAE : Paint coil protection.
- ☐ THD : Defrost thermostat (5709L).
- ☐ THS : Safety thermostat (5708L).
- ☐ 2TH : Defrost and safety thermostats (5709L + 5708L).
- ☐ HG1 : Hot gas (coil: hot gas, drain pan : electrical heaters)
- ☐ DPK : Intermediate drain pan Kit (3C-E .. R/L).

Item : **Item 16**
 Typ : **Cubic**

Model : 3C-E 3245 L (Drawings are only indicative)



In = 5/8 - Out = 7/8