

Solstice® EZ Flush

Technical Information

Introduction

Solstice® EZ Flush is the next-generation cleaning solution from Honeywell to replace HCFC-141b in straight flush (open flush) refrigeration and air conditioning circuits. Solstice EZ Flush is based on Honeywell's hydrofluoro-olefin solvent technologies for solvent degreasing shows an excellent combination of high solvency power with a variety of oils (e.g. mineral, synthetic, and PAG).

- **Environmentally Preferable**
Ultra-low global warming potential (GWP) of 1 and non-ozone-depleting
- **Safe to Use**
Non-flammable¹
- **Trusted Supply**
Ready-to-use alternative to HCFC-141b designed and made in the U.S. by Honeywell, a trusted, global supplier

Applications

Solstice EZ Flush is used to flush and clean the components of air conditioning and refrigeration circuits, including, but not limited to:

- Transportation A/C and refrigeration, such as cars, trucks, buses, and trains
- Aerospace, such as airplanes and helicopters
- Residential and commercial A/C applications
- Commercial refrigeration systems
- Process chillers

Cleaning Effectiveness

Solstice EZ Flush is an effective cleaning solvent for many common oils and lubricants, including, but not limited to:

• Mineral oils	• Heavy grease
• Refrigerant oils	• Cutting oils
• Vacuum oils	• Silicone oils
• Fluorinated oils	• Silicone grease

As with any product, Honeywell recommends testing effectiveness in your application prior to use.



Cleaning Performance

	Typical Refrigerant Lubricants		
	Mineral Oil	POE	PAG
Solstice EZ Flush	Very Good	Very Good	Very Good
Nitrogen	Poor	Poor	Poor
R-22	Good	Good	Good
HCFC-141b	Very Good	Very Good	Very Good

Physical Properties

Chemical Family	Hydrofluoroolefin (HFO)
Appearance	Clear and Colorless
Boiling Point	19°C / 66°F
Liquid Density @ 20°C	1.27 g/mL
Purity	98 wt % +

Safety and Environmental Information

Solstice® EZ Flush is supplied in pressurized cylinders. As with any solvent cleaning process, always exercise caution when handling the cylinders. Avoid direct inhalation or contact with the contents. Ensure the safety of operators and people nearby. Refer to the EZ Flush Safety Data Sheet (SDS) for complete information.

Solstice EZ Flush has an ultra-low GWP of 1 and is non-ozone-depleting. It also has a very low maximum incremental reactivity (MIR), which means that the material will have a low impact on tropospheric ozone, or smog, creation. It is safe to vent EZ Flush directly to atmosphere in accordance with regional and local regulations.

Physical and Environmental Properties

Vapor Flame Limits ¹	None
Flash Point	None
LFL / UFL (Vol %)	None
VOC (U.S. EPA)	Exempt
ODP	Non-ODP ^{2,3}
GWP, Rev. 5 th IPCC, 100 Year	1
WEEL ⁴	800 ppm

Materials Compatibility

Solstice EZ Flush is compatible with stainless steel, cold rolled steel, galvanized steel, copper, iron, and aluminum, with or without excess water.

Pressurization and Usage

Compressed nitrogen can be used to dry the circuit after flushing with Solstice EZ Flush if desired. Avoid using compressed air.

IMPORTANT: Solstice EZ Flush is engineered for single-use application only. It is not compatible with Honeywell Ekoflush™ machine-driven flush units.

Storage and Disposal

Refer to the SDS before using the product. Dispose of empty cylinders in accordance with all federal, state, local and environmental laws and regulations. Avoid storing filled cylinders above 55°C for prolonged periods of time.

Packages

Solstice EZ Flush is available in 10-kg cylinders, pressurized with nitrogen between 6-8 bar, for an easy introduction and evacuation of the solvent through the circuit.



¹Solstice PF is a UN class 2.2 nonflammable liquefied gas. It is designated as nonflammable by ASTM E-681.

²M.P.S. Andersen et al. / Journal of Photochemistry and Photobiology A: Chemistry 199 (2008) 92–97

³K. O. Patten and D. J. Wuebbles / Atmos. Chem. Phys., 10, 10867–10874, 2010

⁴Workplace Environmental Exposure Level (8-hour time-weighted average) per the Occupational Alliance for Risk Science (OARS)

For more information:

www.honeywell-solvents.com/resources
or send an email to
fluorines.europe@honeywell.com

Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.

Honeywell Belgium N.V.

Gaston Geenslaan 14
3001 Heverlee
Belgium
Phone: +32 16 391 211
E-mail: fluorines.europe@honeywell.com

Solstice is a registered trademark of Honeywell International Inc.

©2016 Honeywell International Inc. All rights reserved.

December 2016



Version 1 | 12/2016

© 2016 Honeywell International Inc. All rights reserved.

Honeywell